

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

(10)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 03176053 A

(43) Date of publication of application: 31 . 07 . 81

(51) Int. Cl.

A61F 13/15

A61F 5/44

(21) Application number: 01315742

(71) Applicant: ZUIKOU:KK

(22) Date of filing: 04 . 12 . 89

(72) Inventor: WADA TAKAO


(54) MANUFACTURE OF BRIEFS TYPE DISPOSABLE
DIAPER

COPYRIGHT: (C)1991,JPO&Japlo

(57) Abstract:

PURPOSE: To reduce costs by enabling an automatic large-scale production method by forming a back body wrapping part and front body wrapping sections to place a diaper main body thereon orthogonally and to bond it thereto.

CONSTITUTION: Optional stock is selected for a back body wrapping section and front body wrapping sections (2 and 3) independently of diaper body 1. In other words, the diaper body 1 is relayed to a turning transfer device 7B behind a suction conveying device 7A and the diaper body 1 is turned by 90 to be supplied to a specified position between belt bodies 2a and 3a of both body wrapping sections perpendicular thereto. Then the diaper body is conveyed to a bonding means 8 to bond it integrally with the belt bodies 2a and 3a of both body wrapping sections. Thereafter, the assembly is conveyed to a folding means 9 to be folded double and side ends of the belt bodies 2a and 2b of both the body wrapping sections are cut while being bonded by a bonding/cutting means 10.



*full translation attached
No equivs. outside Japan*

Japanese Patent Office (J P)
LAID OPEN PATENTS GAZETTE (A)

Laid open July 31, 1991

INT. CL'

A 61 F

13/15

5/44

Identification code H

Internal office filing numbers 7603-4 C

6606-3B A 41 B 13/02 S

Examination request	not requested
---------------------	---------------

Number of claims 1

(total of 6 pages [in the Japanese])

Title of the invention Brief-type disposable diaper production
method

Patent application number H1-315742

Application date: December 4, 1989

Inventor T. Wada
c/o K.K. Zuiko
15-21 Minami Beppu-cho,
Settsu-shi, Osaka-fu -

- 2 -

Applicant K.K. Zuiko
 15-21 Minami Beppu-cho,
 Settsu-shi, Osaka-fu
Agent Patent attorney F. Okumura

Specification

1. Title of the invention

Brief-type disposable diaper production method

2. Scope of the patent claim

A brief-type disposable diaper production method involving

a process whereby a water-absorbent material is inserted between an outer sheet and an inner sheet to form a diaper body;

a process whereby a front waistband and a continuous back waistband having an elastic member at least at the side is formed;

a process whereby the diaper body is overlapped and adhered to both waistbands in the transverse direction;

a process whereby the diaper body is folded double and both waistbands are brought into contact; and

a process whereby the contacted waistbands are cut to prescribed dimensions and the regions near the cuts are adhered to integrate the waist parts at the edge portions

to produce a brief-type disposable diaper from a diaper body and a single waistband.

3. Detailed description of the invention

- 3 -

Field of industrial use

The present invention relates to a brief-type disposable diaper production method.

Prior art

Known technology relating to this type of brief-type disposable diaper production method is disclosed in Japanese Unexamined Patent Application Number S57-77304: "Diaper-brief and Production Method Therefor".

Problems to be overcome by the invention

The abovementioned technology is disadvantageous in that as there is a cut-out portion in order to form an opening for the wearer to insert his/her legs, it is necessary to add a process for forming the cut-out portion, which raises production costs.

Means of overcoming the abovementioned problem

The present invention overcomes the abovementioned problem of the prior art and allows the production of brief-type disposable diapers by an automated large-scale production method involving a process whereby a diaper body is formed; a process whereby a back waist part and front waist part are formed; a process whereby the diaper body is overlapped and adhered to both waist parts in the transverse direction; and a process whereby the diaper body is adhered and integrated.

Embodiment

The present invention is described in detail based on the embodiment shown in the following drawings.

Figures 4 through 6 show an example of a brief-type disposable diaper produced according to the present invention: 1

- 4 -

represents the diaper body, formed by inserting absorbent material 13 between outer sheet (for example, a water-impermeable P.E. sheet) 11 and inner sheet (for example, water permeable nonwoven cloth) 12.

2 is the back waist part and 3 is the front waist part, and the material for both waist parts 2 and 3 may be selected independently from the material for diaper body 1, although in this embodiment, the same material is used; the double layer having P.E. sheets 21 and 31 as the outside and nonwoven cloth 22 and 32 as the inside is formed, an elastic member sheet (for example, a polyurethane sheet) 23 and 33 is inserted into part thereof, so that at least the upper edge is expandable. It should be noted that it is also possible to have a single layer elastic sheet, to form a completely expandable construction. It should be noted that as waist parts 2 and 3 are preferably of an air-permeable material, it is desirable either to take the nonwoven cloth and elastic sheet, and exclude the P.E. sheet, or, when a P.E. sheet is used, to puncture a plurality of small holes therein. It is also possible to totally or partially affix the elastic member (rubber thread, rubber tape or the like) to a sheet of suitable material, to form an elastic sheet.

Moreover, the hole parts H for the insertion of the wearer's legs are dictated by the width and shape of the diaper body 1 and the width and shape of waist parts 2 and 3, and generally, the shape is such that the holes are toward the front side.

The brief-type disposable diaper production method of the

- 5 -

present invention will be described below with reference to Figures 1 through 3.

Figure a shows the diaper body 1 production process: absorbent body 13 is placed on outer sheet (back sheet) 11 supplied from outer sheet roller 11a, then inner sheet (top sheet) 12, supplied from inner sheet roller 12a, is supplied thereon, to achieve a sandwich-like insertion of absorbent body 1 between outer sheet 11 and inner sheet 12; then this is transported by the first conveyor device 4 to adhering-cutting device 15, and the circumference is firmly adhered by adhering-cutting device 15, or adhered with adhesive, then cut to the required shape. It should be noted that this process is the same as known diaper production processes, and it is possible to employ a conventional production line for disposable diapers.

It should be noted that the adhering-cutting device 15 comprises two stages: first unit 15a and second unit 15b. In first unit 15a, only adhesion and the cutting of cut-away parts P proceeds, to continuously form diaper body 1, then diaper body band 1a is transported to the next process, and may be cut crosswise to the required dimensions by second unit 15b when in the vicinity of the waistbands 2,3-adhesion process.

Moreover, as there are no cut-away parts P when diaper body 1 is long, it is also possible to achieve the aims of the present invention by only adhering in first unit 15a, then cutting in second unit 15b.

There are various possible shapes for the cut-away parts P, and the shape can be selected according to the shape of the

- 6 -

waistband 2,3 and the desired shape of hole parts H.

Figure 1(b) shows a waistband 2, 3 production line: elastic member sheet 23a, supplied by elastic member sheet roller 14, is cut along a continuous S-shaped cutting line in the central portion by cutting device 24 to form a pair of bands, back waistband 2a and front waistband 3a.

It should be noted that in the case of the multilayer constructions shown in Figure 3 (outer sheet (P.E. sheet) and elastic member sheet, inner sheet (nonwoven cloth) and elastic member sheet, or outer sheet and elastic member sheet-inner sheet), if elastic member sheet 23a is a band of the same width, and only part of sheet 21a, 22a is adhered, the elastic member sheet can be used effectively without cut-away parts, and holes of the desired shape can be found by selecting a suitable shape for waist part 2,3.

Figure 1(c) integrates the diaper body 1 process of Figure 1(a) and the waistband 2a, 3a process of Figure 1(b), to show the brief-type disposable diaper-forming process: the second conveying device 5a, 5b for waistbands 2a, 3a extends to become the third conveying device 6A and the force conveying device 6B.

Diaper body supply means 7 comprises suction conveying device 7A and rotation conveying device 7B, such that suction conveying device 7A for conveying the diaper body 1 that has been cut to the required dimensions is provided at the end of the first conveying device 4, after which diaper body 1 proceeds onto rotation conveying device 7B, then rotation conveying device 7B rotates the diaper body 1 through 90°, to supply diaper body 1

- 7 -

transversely to a prescribed position on waistband 2a, 3a.

It should be noted that rotation conveying device 7B receives the diaper body 1 on the conveying surface of suction conveying device 7A then supplies it by rotating 1/4 of a rotation while suction continues, then rotating the diaper body 1 that is between third conveying device 6A and fourth conveying 6B through 90°, and diaper body supply means 7 can achieve the aim by means of a suitable conveying means as follows: the adsorption surface of the diaper body is rotated through 90° according to the rotation of a suction rotation drum provided so as to be continuous with suction conveying device 7A, then the diaper body proceeds to a suction conveyor belt, whereupon it is conveyed in a transverse direction with respect to the conveying devices, thereby allowing diaper body 1 to be supplied between waistbands 2 and 3.

Diaper body 1 is then conveyed to adhesion means 8 and adhered to waistbands 2a, 3a by a suitable adhesion means such as an adhesive or heat seal.

It is then conveyed to folding means 9, and folded double by said folding means 9 to superimpose front waistband 2a and back waistband 3a.

The sides of the superimposed waistbands 2a and 2b are adhered and cut to the required shape by adhering-cutting means 10, to yield brief-type disposable diaper A.

Advantages of the invention

The present invention yields a brief-type disposable diaper by adhering and integrating a pair of waistbands and a

- 8 -

diaper body and cutting to the required dimensions and so conventional diaper production lines can be used for the diaper body, the waist parts are supplied as bands and automated mass production is possible due to a belt conveying device, so the brief-type disposable diapers can be effectively produced at extremely low cost.

4. Brief description of the drawings

Figure 1 is an explanatory diagram for the brief-type disposable diaper production method of the present invention: Figure (a) shows the diaper body production process, and Figure (b) shows the waistband-integrating process.

Figure 2 is a diagram of the diaper body, and Figure 3 shows the front waist part and back waist part.

Figure 4 shows an oblique view of a brief-type disposable diaper produced according to the present invention, Figure 5 is plane view and Figure 6 is a cross-sectional view of the diaper body.

- | | |
|----|--------------------------|
| 1 | Diaper body |
| 2 | Back waist part |
| 3 | Front waist part |
| 7 | Diaper body supply means |
| 8 | Adhesion means |
| 9 | Folding means |
| 10 | Cutting means |

Applicant K.K. Zuiko

Patent attorney

S. Okumura

④日本四符斤(JP)

◎ 許出頭公司

④ 公開特許公報 (A) 平3-176053

⑤Int. Cl. '

識別記号

厅内整理番号

④公開 平成3年(1991)7月31日

A 61 F. 13/15
5/44

H

7603-4C
6606-3B

A 41 8 13/02

3

香蓬請求 来請求 隔来頃の改し (全6頁)

④発明の名称 **ブリーフ足使い捨ておむつの製造方法**

② 平1-315742

出 票 日 期 1989 年 12 月 4 日

田 明 香 和 田 隆 男 大阪府津市南別府町15番21号 株式会社光栄内

④出 願 人 株 式 金 辻 道 光 大 阪 府 高 津 市 南 別 府 町 15 番 21 号

④代理人 赤野士 櫻村 文雄

— — —

୧. ସ୍ୱାଧୀନତା

ブリーフは正しい着せ方の要領が

३. नमो भगवते वासुदेवाय

外置シートと内蔵シートとの間に緩衝板を設け、
 込んで利用する工法とする。

十分くこもぬれ玉に其の面影を映すも直ぐ其の
 面影の影を映すは如く上づぬれ玉の面影は其の
 面影をも工なり。

[illegible]

、其のつとめを二階に附け、其のともにも成
りて、其のつとめを附け、其のともにも成

利用した炭素源の生産コストを算定するために作成した
この明確な炭素のフローを把握して炭素源の量を削減
することで一掃化する工夫と。

を食ふ。あつたて、一匹の飼育係の
によつて、アリーフの皮を剥いてあつたてを
を剥いてあつたてを剥いてあつたての皮
を剥いてあつたてを剥いてあつたての皮

3. 親戚の家族生活

○ 農 業 上 の 利 用 分 野

五段組立、ブリーフ用紙に附て其のつの製造方法に随するものである。

○ ○ ○ ○ ○

この風のブリーフは使っていておつた製造方法に就し、製造は31-113044「おしのブリーフおよびその製造方法」の公開特許が得た。

○ 〇 〇 〇 〇 〇 〇 〇 〇 〇 〇 〇 〇 〇 〇 〇 〇


上記の電報文句においては、費用に於たり是則
 費の支を個人するたのの該口紙を形成するたのの
 明大紙分が作成するたの、明大紙分を形成するた
 のの工賃を所算する必要があり、又該コストが明
 大である必要があり、

○上は原典・複製とその他の手紙


本報では、各々の主張を形成する工程と、所司
が選り取らるゝの過程を形成する工程と、
各報の互に押し合はるゝに依つて主張を整理し
形成する工程と、各々の主張を同時一様化する工
程とによる、多面的な整理過程によつて、一

特開平3-176053(4)

第1図 (a)




第1図 (b)




特開平3-176053(5)


第1図(C)



第2図




第3図



13 00 3-170053 (6)

第4图



第6图

